


## IsoTemp Solution on Ram ProMaster



### Fully Integrated & Climate Controlled Cargo Isolation System



Customizable with up to 3 separate temperature controlled environments from -5°F to 60°F

Ideal for applications including:

- Food Delivery
- Biomedical Transport
- Catering

\*ATP & HACCP Certified



### STANDARD EQUIPMENT

- Modular, insulated fiberglass panels
- Non-slip floor
- Fully insulated doors
- Floor drain
- Interior lighting (LED ceiling light)

### PRODUCT FEATURES

- Modular kit assembly for high volume upfits
- Best-in-class thermal insulation
- Fiberglass panels are leak-free and easy to clean

### SPECIFICATIONS

Wheelbase	Roof Variants	Cargo Area Volume	Inner Length	Inner Width	Inner Height
136	High (H2)	272 cubic ft.	111.2"	63.8"	69.3"
159	High (H2)	328.4 cubic ft.	134.2"	63.8"	69.3"
159 Extended	High (H2)	363.8 cubic ft.	145.6"	63.8"	69.3"

\*Full range of insulation solutions as above mentioned for units equipped with right, left sliding door or both

### CLIMATE CONTROL SYSTEM

- Industry standard cooling units available from multiple manufacturers

## IsoTemp Solution on Ram ProMaster

### OPTIONS



- Aluminum fold-down shelves



- Clear PVC strip curtains
- Available for side or rear doors




- Stainless steel doorstep protection
- Floor drain (standard)



- Anti-slip aluminum floor protection



- Extra side door for frozen transport



- Aluminum low side wall protection

## IsoTemp Solution on Ram ProMaster

### Thermo King Reefer Application

				Thermo King Direct Drive Application			
				10 Door Openings Per Day		30 Door Openings Per Day	
Van Make	Van Model	Wheelbase	Roof Height	Fresh (35°F)	Frozen (-4°F)	Fresh (35°F)	Frozen (-4°F)
Ram	ProMaster	136 in. (Regular)	High	V200	V300 Max	V200	V520 Max
		159 in. (Long)	High	V200	V520 Max	V300	V520 Max
		159 in. (Long Extended)	High	V200	V520 Max	V300	V520 Max

\*Outside temperature up to 104°F. Check with your sales representative for outside temperatures over 104°F.

\*\*Standard units have suffix "10." The "10" series does not offer power standby.


\*\*\*Shore power units are represented with suffix "20." The "20" series is offered with 115/1/60 Hz, 220/1/60 Hz or 230/3/60 Hz power standby options.

### Zanotti Reefer Application

				Zanotti Application	
				30 Door Openings Per Day	
Van Make	Van Model	Wheelbase	Roof Height	Fresh (35°F)	Frozen (-4°F)
Ram	ProMaster	136 in. (Regular)	High	Z350	Z380X
		159 in. (Long)	High	Z380	Z380X
		159 in. (Long Extended)	High	Z380	Z380X

\*Outside temperature up to 104°F. Check with your sales representative for outside temperatures over 104°F.

\*\*All units represented in this matrix include standby option.



- Gruau with TKV200, 61.8% less powerful than the TK320 of competitors

- Gruau operated on idle offering less than 60% of TK200 capacity while the others operated on stand by

- Gruau started with 107F and cooled to 34.6 F in 2h 37m (157 minutes)

- Competitor #1 & #2 never reached 35°F fresh despite a more powerful V320 unit.

## About Gruau

Gruau is a French, 5th generation family-owned company that has been in business for over 126 years, specializing in the conversions of light commercial vehicles. With over 1,600 employees and 50,000 conversions per year for customers and OEMs around the world, Gruau is Europe's leading body builder. Its 18 commercial and industrial facilities offer unique design, commercial and industrial capacity.



Gruau is expanding its network with long term quality partners that have been trained both technically and commercially.

**Please contact us for more information**

Michel MENIL – CEO

✉ [michel.menil@gruau.com](mailto:michel.menil@gruau.com)